

## SN-356 Feature List

Feature		SN-356
Photo		
1	Frequency	268MHz ~ 394MHz (F9)
2	Long Range Cordless	8 - 15Km
3	Multi-channel with auto-scan	○
4	Multi-handset system (up to 99)	○
5	Single Color LCD(Orange)	○
6	Walkie-talkie between H/S	○
7	Vibration mode	×
8	Selectable Ring & Page Tone on H/S & B/S	H/S : 15
9	H/S with speakerphone function	○
10	H/S with scrolling keys	○
11	Two-way paging & hand-free intercom	○
12	H/S Custom Name Edit	○
13	30 CID memory with Time/Date (FSK & DTMF type)	○
14	CID with call waiting (CIDCW)	○
15	Last 10 calls redial on H/S	○
16	50 Phonebook with name/number on each H/S	○
17	Tone/Pulse dialing mode selectable	○
18	Multi-language display	English / Russian / Arabic / Spanish / Turkish
19	Music on hold	×
20	B/S speakerphone with dial keypad	×
21	20 memory dial on B/S	×
22	B/S unit with last number redial	×
23	LCD and H/S keypad with backlit	○
24	Auto detection of FSK and DTMF CID signal	○
25	Change channel during Conversation	○

26	65,536 sets security codes (two-way)	○
27	Flash time programmable	○
28	Ring volume adjustable for H/S	○
29	Voice volume adjustable for H/S	○
30	H/S with power saving function	○
31	Low battery alert and display	○
32	Built- in voice security circuit (Scrambler)	○
33	Auto answer and auto hang up	○
34	Transferring a call between H/S and B/S	x
35	Out-of-range alert	○
36	Battery charge indicator	○
37	Fast charge	○
38	Adjustable Keypad volume on H/S	○
39	Auto power control designed	○
40	H/S key	
41	-Talk	○
42	-End	○
43	-Power on/off	Built-in “End”
44	-Flash	Built-in “Talk”
45	-Up/Down	○
46	-Softkey	2
47	-Intercom	○
48	-PTT	○
49	-Speakerphone	○
50	-Caller ID	○
51	-0~9, *, #	○
52	B/S key	
53	-Vol Up/Down	○
54	-Intercom	○
55	System Package :	
56	* Handset x 1	○
57	* Base x 1	○
58	* Battery(1050mAh/3.7V Li-Ion) x 1	○
59	* Line cord(RJ-11) x 1	○
60	* Power Adaptor x 1	○
61	* User Manual x 1 (CD)	○
62	* Base antenna x 1	○

63	* Installation CD x 1	
64	Handset Package :	
65	* Handset x 1	○
66	* Battery(1050mAh/3.7V Li-Ion) x 1	○
67	* Travel charger x 1	○
68	* Quick Guide x 1	○

	<b>Base station</b>	<b>Handset</b>
<b>Transmitter</b>		
Frequency	394 MHz	268 MHz
Output power	1 W	450 m W
Spurious emission	55 dBc	55 dBc
Current consumption		
Stand-by	100 mA	10 mA
Talk	600 mA	420 mA
<b>Receiver</b>		
Frequency	268 MHz	394 MHz
Sensitivity at 12 dB SINAD (CCITT)	-122dBm	-121dBm
Adjacent channel rejection	50 dBc	50 dBc
Spurious response	55 dBc	55 dBc
Power source	AC 110V/220V, 50/60 Hz DC 12V/800mA	3.7V/1050 mAh Li-Ion Battery